Oiva FIL 4.2W 15000h BX

Pure white light - dimmable

The Oiva lamp series covers all typical residential lighting needs. The tone is a pleasant pure white (3000 K). The opal light source provides non-glaring light. These small and light lamps replace incandescent bulbs and halogen lamps. The eco-friendly cardboard packages are colour-coded. The colour indicates the corresponding incandescent bulb, making the choice simpler for the consumer. Technical specifications are also clearly presented.

Opal classic dimmable LED lamp 4.2W 3000K E27 470lm 15000h 60x108mm, cardboard packing. Supply frequency ~50/60Hz.

FIL 4.2W 15000h BX			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
9410835	A7GAPP	0.032	Oiva



AIRAM

FIL 4.2W 15000h BX EC001959

Mounting	
Degree of protection (IP)	Other
Structure	
Colour	White
Housing colour	White
Energy efficiency class	E
Dimming and control	
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	No
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Photometric data	
Luminous flux (min) (lm)	470
Luminous flux (max) (lm)	470
Colour rendering index CRI	80-89
Colour of light acc. EN 12464-1	Warm <3300 K
Colour temperature (min) (K)	3000
Colour temperature (max) (K)	3000
Beam angle (min)	360
Beam angle (max)	360
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG1
Lifetime and capacity	
Measurements	
Measurements Diameter (mm)	60
Measurements	60 108
Measurements Diameter (mm) Length (mm)	
Measurements Diameter (mm) Length (mm) Electrotechnical data	108
Measurements Diameter (mm) Length (mm) Electrotechnical data Nominal voltage (min) (V)	108 220
Measurements Diameter (mm) Length (mm) Electrotechnical data Nominal voltage (min) (V) Nominal voltage (max) (V)	108 220 240
Measurements Diameter (mm) Length (mm) Electrotechnical data Nominal voltage (min) (V) Nominal voltage (max) (V) Nominal current (min) (mA)	108 220 240 25
Measurements Diameter (mm) Length (mm) Electrotechnical data Nominal voltage (min) (V) Nominal voltage (max) (V) Nominal current (min) (mA) Nominal current (max) (mA)	108 220 240 25 27
Measurements Diameter (mm) Length (mm) Electrotechnical data Nominal voltage (min) (V) Nominal voltage (max) (V) Nominal current (min) (mA) Nominal current (max) (mA) Power factor	108 220 240 25 27 0.7
Measurements Diameter (mm) Length (mm) Electrotechnical data Nominal voltage (min) (V) Nominal voltage (max) (V) Nominal current (min) (mA) Nominal current (max) (mA)	108 220 240 25 27

