

# Oiva

## FIL 9W 15000h BX

Pure white light - dimmable

The Oiva lamp series covers all typical residential lighting needs. The tone is a pleasant pure white (3000 K). The opal light source provides non-glaring light. These small and light lamps replace incandescent bulbs and halogen lamps. The eco-friendly cardboard packages are colour-coded. The colour indicates the corresponding incandescent bulb, making the choice simpler for the consumer. Technical specifications are also clearly presented.

Opal classic dimmable LED lamp 9W 3000K E27  
1055lm 15000h 60x108mm, cardboard packing. Supply frequency ~50/60Hz.



| FIL 9W 15000h BX |        |       |                |
|------------------|--------|-------|----------------|
| PRODUCT CODE     | CODE   | KG    | PRODUCT FAMILY |
| 9410836          | A7GAPQ | 0.038 | Oiva           |

| Mounting                  |       |
|---------------------------|-------|
| Degree of protection (IP) | Other |

| Structure               |       |
|-------------------------|-------|
| Colour                  | White |
| Housing colour          | White |
| Energy efficiency class | E     |

| Dimming and control              |    |
|----------------------------------|----|
| Dimming Touch and Dim            | No |
| Dimming Zigbee                   | No |
| Dimming Bluetooth                | No |
| Dimming Wi-Fi                    | No |
| No dimming function              | No |
| Remote operation possible        | No |
| With movement sensor             | No |
| With remote control              | No |
| With twilight switch             | No |
| Compatible with Apple HomeKit    | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa     | No |
| IFTTT support available          | No |

| Photometric data                             |              |
|--|--------------|
| Luminous flux (min) (lm)                     | 1055         |
| Luminous flux (max) (lm)                     | 1055         |
| Colour rendering index CRI                   | 80-89        |
| Colour of light acc. EN 12464-1              | Warm <3300 K |
| Colour temperature (min) (K)                 | 3000         |
| Colour temperature (max) (K)                 | 3000         |
| Beam angle (min)                             | 360          |
| Beam angle (max)                             | 360          |
| Colour consistency (McAdam ellipse)          | SDCM6        |
| Photobiological safety according to EN 62471 | RG1          |

#### Lifetime and capacity

| Measurements  |     |
|---------------|-----|
| Diameter (mm) | 60  |
| Length (mm)   | 108 |

| Electrotechnical data      |     |
|----------------------------|-----|
| Nominal voltage (min) (V)  | 220 |
| Nominal voltage (max) (V)  | 240 |
| Nominal current (min) (mA) | 49  |
| Nominal current (max) (mA) | 55  |
| Power factor               | 0.7 |
| Voltage type               | AC  |