



DATA SHEET

STARLIGHT SETS 1527460; 1527464; 1527461; 1527465

VPAC-1530-CEP100

VPAC-1530-CEP200

VPAC-1540-CEP100

VPAC-1540-CEP200



Sets with CEP100 fibre harness:

This set is especially suited for creating small or medium-size starlight ceilings of approx. 2-3 m². The fibres of the set are plastic and tolerate temperatures of up to 80 °C. The fibres of this set may not be installed in a sauna. However, they are suitable for steam rooms and infra-red saunas, in which the temperature remains below 80 °C.

You can choose a colour temperature of 3000K or 4000K. The projector of this set is completely silent with no noisy fan.

The complete ready-to-install set includes a projector and a bundle of fibres. Fibre size \varnothing 0.75 mm, numbers and lengths as follows:

50 x 2,5 m

50 x 3,0 m

The black cover of the fibre can be peeled off for the required length and the fibres can be cut at the installation. The installation instructions can be downloaded from the website

www.cariitti.fi/en/collections. The fibres are maintenance-free after the installation.

Sets with CEP200 fibre harness:

This set is especially suited for creating medium-size starlight ceilings of approx. 4-6 m². The fibres of the set are plastic and tolerate temperatures of up to +80°C. The fibres of this set may not be installed in a

CARIITTI OY

Niittyrinne 2B FI-02270 Espoo Finland

Tel.int. +358-9-221 9040

sales@cariitti.com

www.cariitti.com

VAT FI11098066

Business ID

1109806-6



DATA SHEET

sauna. However, they are suitable for steam rooms and infra-red saunas, in which the temperature remains below +80°C.

The projector of this set is completely silent with no noisy fan. The light source is a 15 W led with cold white light.

The complete ready-to-install set includes a projector and a bundle of fibres. Fibre size \varnothing 0.75 mm, numbers and lengths as follows:

50 x 2,5 m

50 x 3,0 m

50 x 3,5 m

50 x 4,0 m

The black cover of the fibre can be peeled off for the required length and the fibres can be cut at the installation. The installation instructions can be downloaded from the website

www.cariitti.fi/en/collections. The fibres are maintenance-free after the installation.

The projectors in these set are:

VPAC LED projector, 3000K 1801002

VPAC LED projector, 4000K 1801003



VPAC40 LED projector is suitable for use with both glass and plastic fibres. The projector has a protection class of IP65 and can also be installed on the sauna wall, under the benches.

Choose a colour temperature is 3000K / 4000 K (warm/cold white light), no twinkle effect. Technical characteristics:

CARIITTI OY

Niittyrinne 2B FI-02270 Espoo Finland

Tel.int. +358-9-221 9040

sales@cariitti.com

www.cariitti.com

VAT FI11098066

Business ID

1109806-6



DATA SHEET

- 230V
- 16.5 W
- 1500 lm, Ra > 90
- L 145 x W 150 x H 83
- LED, 50,000h
- Dimming from the supply voltage
- IP65
- Weight 1,03 kg
- Fibre harness mounting hole \varnothing 30 mm

Fibre harnesses with the common end \varnothing 30 mm can be attached directly to this projector.
The maintenance of the projector: the projector is recommended to be installed with easy access.

In case of malfunction, please contact the seller or the manufacturer for evaluation of repair.

If case the LED component needs to be replaced, the following spare parts are available:

1801004	LED mounting platform for VPAC27 2700K
1801005	LED mounting platform for VPAC30 3000K
1801006	LED mounting platform for VPAC40 4000K